

IMT RECOMMENDED LUBRICANTS AND COOLING FLUIDS

LURICATION POINT	APPLICABLE STANDARD	CHANGING INTERVAL HRS.	BP	ESSO	MOBIL	TEXACO	SHELL	TOTAL
ENGINE	JUS B.H.3. 169 TIP D MIL-L2104C FROM-18c TO 0 C. SAE 10 FROM 0C-30C OVER 25C SAE 30 ALL TEMP.15W-40	200	VANELUS C3 OR ENERGOL DS-3	ESSOLUBE D3	DELVAC OIL 1300	URSA OIL LA-3, OR PRUDELO-300	MYRINA OR RIMULA-CT	RUBLA-5
TRANSMISSION, REAR AXLE AND HYDRALICS	MF-1135 JD14B FORD-ESEN M2C 86A	800 OR ONCE PER YEAR	HYDRALIC TF-9	TORQUE FLUID 56	MOBILE FLUID 422	AS TRANSMISSION OIL JD 303	DONAX-T.12	TRANSMISSION JD OR TRANSMISSION MF
STEERING WORM GEAR IN STEERING HOUSING	MF-1135 JD14B FORD-ESEN M2C 86A	800	HYDRALIC TF-9	TORQUE FLUID 56	MOBILE FLUID 422	AS TRANSMISSION OIL JD 303	DONAX-T.12	TRANSMISSION JD OR TRANSMISSION MF
SERVO STEERING UNIT	AUTOMATIC TRANSMISSION OIL, TYPE A, SUFFIX A, DEXTRON-B	600	AUTRAN GM-PM	AUTOMATIC TRANSMISSION FLUID	MOBIL ATF-200, 220	TEXAMATIC FLUID, DEXTRON-II	ATF DEXTRON II	DEXTRON
ALL GREASED LUBRICATED POINTS	Li BASE GREASE, NLGGI-2, JUS B H3 634		ENERGREASE LS-2	MULTIPURPOSE GREASE-H	MOBIL GREASE MP	MARFAK MULTI PURPOSE-2	RETINAX	TOTAL MULTIS
COOLING SYSTEM WINTER	JUS H 22. 010		ANTIFREEZE COOLANT UT-184	ANTIFREEZE	MOBIL ANTI-FREEZE	ANTIFREEZE	GLYCOSHELL P300	TOTAL ANTIGEL